

Midilift DL

The Stannah Midilift DL platform lift provides external vertical travel access, up to 12m, carrying passengers simply and safely over several levels.



All our Midilifts will help building owners/operators to meet the requirements of:

- The Disability Discrimination Act (DDA)
- Part M of the Building Regulations (England and Wales) and Section 4.2 of the Technical Handbook (Scotland), both of which cover the requirements that many new buildings must meet to ensure ease of access and use
- BS 8300:2009 Code of Practice covering the design of buildings and their approaches to meet the needs of disabled people

All of our Midilifts are CE marked and comply with the latest Machinery Directive 2006/42/EC.

The Midilift DL is designed to give customers choice and flexibility. This external solution is ideal for sites where there is limited internal space, providing a partially enclosed cabin with its own external structured enclosure.

Standard features

- 900mm clear opening at each entrance
- Steel landing door with vision panel
- Emergency lowering provided by back up battery
- Emergency alarm with back up battery
- Audible and visual notification of floor level and travel direction
- Two tone arrival chime at each landing
- Overload indicator
- Keyswitch to isolate the lift at the main floor

Optional features

- Panoramic glazed landing doors
- Steel fire rated landing doors
- Powered landing doors
- Digital position indicators on each landing
- Key operated controls at each landing
- Intercom system
- Autodialler telephone
- One touch controls on landing and lift car

Stannah

Midilift DL




Data sheets giving further technical information are available – please call 01264 339090 for a copy. Alternatively, you can download a PDF from our web site at www.stannahlifts.co.uk/downloads

If your building needs a lift for frequent travel by many users a conventional passenger lift may be more suitable. Please contact us if you require advice on selecting the most appropriate solution for your needs.

Midilift DL key features

- Three platform sizes (w x d)
900mm x 1200mm
900mm x 1400mm[#]
1100mm x 1400mm[#]
- Structure supported enclosure – no lifting beam required
- Up to 12m travel
- Multiple stops
- Partially enclosed cabin
- Internal entrances available on three sides
- Easy to use constant pressure push button controls
- Particularly suitable to external installations
- Range of finishes available
- 12 month warranty

TECHNICAL SPECIFICATION:

Standard load	350kg
Speed of travel	0.15m/s
Drive system	Single speed hydraulic
Control system	Constant pressure
Power supply	240v single phase

DIMENSIONS:

Sizes:	Platform size (w x d)	Footprint size (w x d)
	900 x 1200	1475 x 1590
	900 x 1400 [#]	1475 x 1790
	1100 x 1400 [#]	1675 x 1790
Pit depth*	100	
Headroom	2700	

Notes: All dimensions in mm # Part M (England and Wales)

* Depth increases by 50mm for through entrance arrangement. Ramp can be specified if there is no suitable space for a pit.

We are continually developing and improving our range of products and finishes and we therefore reserve the right to alter or amend or amend the specification without prior notice.

Stannah Lifts

Anton Mill, Andover, Hampshire SP10 2NX

Tel: 01264 339090

www.stannahlifts.co.uk

Stannah